

City of Yakima Notes on use of WSDOT Standard Plans for Storm Drainage

Use of all WSDOT Standard Plans for “Drainage, Structures and Hydraulics” are approved for use by the City of Yakima **EXCEPT** the following:

Standard Plan	Standard Plan Title
B-10.70-03	Catch Basin T- PVC
B-30.50-03	Rectangular Herringbone Grate
B-85.10-01	Vertical Connection (for Sanitary Sewer Use)
B-85.20-00	Side Sewer Connection (for Sanitary Sewer Use)
B-85.30-00	Standing Side Sewer Connection (for Sanitary Sewer Use)
B-85.40-00	8 Inch Sewer Clean-Out (for Sanitary Sewer Use)
B-85.50-01	Drop Connections (for Sanitary Sewer Use)
B-90.10-00	Hydrant Setting Types A and B
B-90.20-00	2 Inch Blowoff Assembly
B-90.30-00	Combination Air Release / Air Vacuum Valve Assembly
B-90.40-01	Concrete Thrust Block
B-90.50-00	Concrete Thrust Block for Convex Vertical Bends
B-95.20-02	Median Barrier Drainage Installation
B-95.40-01	Inlet Placement at Bridge End

All of WSDOT Standard Plans for “Site Preservation and Erosion Control” are approved for use by the City of Yakima

Additional Note:

Only Below Inlet Grate Devices shall be used for storm drain inlet protection.

The use of felt or other fabrics for storm drain inlet protection is prohibited.